

Husqvarna K 1270 Rail

Cutting a rail track takes power, precision and speed. The K 1270 Rail is the market's most powerful cutter, customised for railways, tram tracks and metro systems. It cuts fast and straight, the attachment mounts quickly to the rail and the double attachment mountings means you can cut from any direction.

Engine	
Output power	5.8 kW
Cylinder displacement	118.8 cm^3
Electrode gap	0.5 mm
Cylinders	1
Number of strokes	2-stroke engine
Exhaust emissions (CO2 EU V)	726 g/kWh

Sound and noise	
Sound power level, guaranteed (LWA)	117 dB(A)
Sound pressure level at operators ear	104 dB(A)

Cutting equipment	
Cutting depth, max	118 mm
Blade diameter, max	350 mm
Arbor diameter	25,4 mm
Blade thickness, max	5 mm
Peripheral speed, max	90 m/s

Dimensions	
Product size length	742 mm
Product size width	241 mm
Product size height	439 mm
Weight	15.3 kg

Vibrations	
Vibrations left/front handle	3.4 m/s^2
Vibrations right/rear handle	3.5 m/s^2

Articles for K 1270 Rail

POWER CUTTER K 1270 Rail 14" | 1" | RA10	967 98 19-01
POWER CUTTER K 1270 Rail 14" | 1" | RA10 | Kil.S	967 98 20-01
POWER CUTTER K 1270 Rail 16" | 1" | RA10	967 98 23-01

Features for K 1270 Rail

Easy to start

The unique design of the carburettor, cylinder and digital ignition system, together with air purge and decompression valve ensure an easy start.



Anti-vibration system

Reduced vibrations in the cutter handle for more comfort and longer operation periods.



Perfect right-angle cuts

The RA 10 attachment fastens to the track to ensure a perfect right-angle cut.



Cutting from both sides

The RA 10 attachment is included as standard and allows cutting from both sides of the track.



Accessories for K 1270 Rail



Two stroke oil, HP



Two stroke oil, HP

Check website for more accessories.

Husqvarna®

http://www.husqvarnacp.com